

AutoLift HE Hostile Environment Stainless Steel Low-Profile Lift Floor Scale



APPROVALS



STANDARD FEATURES

- Rugged washdown design
- 304 stainless steel construction
- Rigid 304 stainless steel channel frame
- Manual, drop-in-place, safety bar
- Four stainless steel, welded seal, shear beam load cells
- Load cells protected on all four sides
- 20 ft of SURVIVOR® hostile environment load cell cable
- Remote TuffSeal® JB4SS stainless steel NEMA 4X junction box
- Smooth stainless steel deck
- Four adjustable stainless steel SUREFOOT™ support feet
- Requires 85-100 psi air pressure

SPECIFICATIONS

End Load Capacity:

100% full scale at 2,000 lb and 5,000 lb
80% full scale at 10,000 lb

Cable Length:

20 ft (6.1 m)

Welding:

Stitch, consult factory if continuous is required

Warranty:

AutoLift HE weldment five years, load cells two years, all other components one year

AutoLift HE Hostile Environment Stainless Steel Low-Profile Lift Floor Scale

PART NUMBER/PRICE

PART #	SIZE (W X L)	CAPACITY	EST. SHIP WEIGHT	PRICE
42207	4 ft x 4 ft	2,000 lb (1,000 kg)	640 lb	Consult
42208	4 ft x 4 ft	5,000 lb (2,500 kg)	640 lb	Consult
42209	4 ft x 4 ft	10,000 lb (5,000 kg)	750 lb	Consult
42211	5 ft x 5 ft	2,000 lb (1,000 kg)	830 lb	Consult
42212	5 ft x 5 ft	5,000 lb (2,500 kg)	830 lb	Consult
42213	5 ft x 5 ft	10,000 lb (5,000 kg)	1,050 lb	Consult

OPTIONS/ACCESSORIES

PART #	DESCRIPTION	PRICE
Consult	Four drilled deck holes for scale height adjustment	Consult
28740	Floor stand for indicator, 36.3 in high stainless steel	Consult

